

KXF600



VENTILATED UPRIGHT STAINLESS STEEL GASTRONORM REFRIGERATION

Description

Available in a single or double door configuration, the KXR/KXF units feature a 201 stainless steel exterior and interior. Rounded corners allow the units to be easily cleaned and maintained only helped by the ability to easily move them around thanks to the heavy duty castors that are fitted as standard on all configurations.

Self-closing doors with dwell position, 3 adjustable shelves per door, 60mm thick insulation, led lighting and more all contribute to this amazing value products success.



Features

- 201 stainless steel exterior & interior
- Internal corners rounded to aid cleaning
- 3 adjustable GN2/1 shelves supplied per door, shelf size 535 x 650 mm
- LED lighting
- Lock fitted as standard
- Heavy duty castors as standard
- Suitable for fresh meat storage
- Self closing door(s) with dwell position

MODEL	DOORS	SHELVES	GROSS CAPACITY	REFRIGERANT	TEMPERATURE RANGE	DIMENSIONS (mm)	ENERGY RATING	POWER USAGE	KWH/ ANNUM	POWER	WEIGHT (kg)
KXR600	1	3	600L	R290	-2°C / +8°C	H2000 x W680 x D840	D	195W	815	13amp	125
KXF600	1	3	600L	R290	-18°C / -22°C	H2000 x W680 x D840	E	450W	2826	13amp	132
KXR1200	2	6	1200L	R290	-2°C / +8°C	H2000 x W1340 x D840	D	380W	1382	13amp	213
KXF1200	2	6	1200L	R290	-18°C / -22°C	H2000 x W1340 x D840	E	700W	4317	13amp	221

OPTIONAL EXTRAS
(Applicable Units)

Shelf & guide pair

Gasket