



KXRC2

Dimensions (mm)	External	Internal
Height	850	564
Width	1360	799
Depth	700	580
Capacity (ltr)		
Gross		282
Net		186



KXRC3

Dimensions (mm)	External	Internal
Height	850	564
Width	1795	799
Depth	700	580
Capacity (ltr)		
Gross		417
Net		311

Features

Stainless steel exterior & interior

Even air distribution by ducted system

Heavy duty castors as standard

Internal corners rounded for easy cleaning

1 x adjustable GN1/1 shelf per door

Self closing doors with dwell position

Replaceable door gasket

Additional Extras

K8-SHELF03 - Shelf for KXR2/3

K8-GUIDE02 - Left hand shelf guide

K8-GUIDE03 - Right hand shelf guide

X1-CATORKIT2 - Castor kit for KXRC2

X1-CASTORKIT3 - Castor kit for KXRC3

K8-GASKET04 - Door gasket



Technical Specification

	KXRC2	KXRC3
Temperature Range	+2°C ~ +8°C	+2°C ~ +8°C
Climate Class	4	4
Power Supply	13amp	13amp
Cooling	Ventilated	Ventilated
Defrost	Automatic	Automatic
Noise Level	48db	48db
Refrigerant	R290	R290
Energy Efficiency Class	C	C
Energy Consumption (kw/24hrs)	2.253	3.184
Power Usage (w)	215	230
Weight (kg)	128	154